



Gliderol™ Heavy Duty & Fire Rated Shutters

Industrial roller shutters



Front page & above
Heavy Duty Roller Shutter
in Monument

Right
Fire Rated Shutter
during testing



Gliderol Heavy Duty & Fire Rated Shutters

Industrial roller shutters

Heavy Duty Roller Shutters

DESIGNED TO CLOSE OPENINGS OF UP TO 7M HIGH X 12M WIDE IN A SINGLE SPAN, GLIDEROL'S COMPREHENSIVE RANGE OF ROLLER SHUTTERS IS PERFECT FOR COMMERCIAL SITES. GLIDEROL CAN ALSO BUILD SPECIAL MODELS FOR LARGER OPENINGS.

Gliderol Heavy Duty Shutters are available in several curtain types to suit different applications and requirements including steel and perforated shutter slats. Gliderol shutters are available in a galvanised finish and can also be powder coated in a colour of your choosing if required.

Gliderol Heavy Duty Roller Shutters are tested to meet the performance criteria set by recognised standards as regulated by Australian and international authorities. All Gliderol shutters are designed and manufactured for Australian conditions. Gliderol also offers a free measure and quote service in all major states and territories.

Features & Benefits

- Suits large openings
- Available in several curtain types
- Various options available
- Australian owned and made
- Free measure and quote

Fire Rated Roller Shutters

GLIDEROL MANUFACTURES THE MOST COMPREHENSIVE RANGE OF FIRE RATED ROLLER SHUTTERS IN AUSTRALIA.

Primarily designed to compartmentalise the spread of flames, fire rated shutters are used to protect contents from burning during fire situations. Available in both two hour and four hour fire ratings, Gliderol's Fire Rated Shutters can be equipped with various detection devices to suit a range of requirements.

Designed and manufactured for Australian conditions and engineered for longevity, Gliderol's Fire Rated Shutters have been tested to the highest standards and are certified by numerous independent bodies including Branz, Warrington and CSIRO. Gliderol offers a free measure and quote service in all major states and territories.

Features & Benefits

- Australian owned and made
- Reduce fire spread
- Fire rated up to two–four hours
- Manufactured to Australian standards
- Free measure and quote

Independently tested by



Test Report FCO-2639



Test Report 21681



Test Report FR3964 & FAR3190/3



Members





Australian Offices

South Australia

Head Office

32 Jacobsen Crescent
Holden Hill SA 5088
Telephone: (08) 8261 9633
Facsimile: (08) 8266 4712

Service & Installation Centre
51 Jacobsen Crescent
Holden Hill SA 5088
Telephone: (08) 8261 9633
Facsimile: (08) 8266 4712

New South Wales

45 Sammut Street
Smithfield NSW 2164
Telephone: (02) 9725 1033
Facsimile: (02) 9725 1115

19 Balook Drive
Beresfield NSW 2322
Telephone: (02) 4966 8500
Facsimile: (02) 4966 8511

Unit 2, 1 Luso Drive
Unanderra NSW 2526
Telephone: (02) 4272 3220
Facsimile: (02) 4272 3084

Queensland

241 Elliott Road
Banyo QLD 4014
Telephone: (07) 3260 9000
Facsimile: (07) 3260 9055

Unit 1, 9 Ramly Drive
Burleigh Heads QLD 4220
Telephone: (07) 5508 7400
Facsimile: (07) 5508 7444

Victoria

23 Kitchen Road
Dandenong VIC 3175
Telephone: (03) 9793 5455
Facsimile: (03) 9706 8492

35 Leather Street
Geelong VIC 3215
Telephone: (03) 5224 2499
Facsimile: (03) 5224 1299

Western Australia

Unit 7, 33 Denning Road
Bunbury WA 6230
Telephone: (08) 9721 7600
Facsimile: (08) 9791 7611

21 Prindiville Drive
Wangara WA 6065
Telephone: (08) 9409 3000
Facsimile: (08) 9409 3200

Tasmania

C/o 23 Kitchen Road
Dandenong VIC 3175
Telephone: (03) 9793 5455
Facsimile: (03) 9706 8492