

WeatherDrive™

IDEAL FOR POWERING SHEDS AND CARPORT ROLLER DOORS



ROLLER GARAGE DOOR OPENER MYQ CAPABLE

KEY FEATURES

WEATHER RESISTANT

Market leading IP34 rated housing to help protect from the elements.

LIFTING POWER

Powers doors up to 100 kg.

MYQ CAPABLE

Opener is myQ capable with additional purchase of Safety IR Beams & myQ Gateway.¹



Compliant to Australian and New Zealand Standard AS/NZS 60335.2.95

SMART



MYQ CAPABLE TECHNOLOGY lets users create schedules, monitor, receive alerts and control the garage door opener away from home.¹



SOFT-START AND SOFT-STOP for smooth operation.

QUIET & RELIABLE



3-YEAR WARRANTY



WEATHER RESISTANT Market leading IP34 rated housing to help protect from the elements.



QUIET DC MOTOR eliminates noise and vibrations through the ceiling and provide smooth operation.



HEAVY-LIFTING POWER operates doors up to 100 kgs.

SAFE & SECURE



SECURITY+ 2.0® sends a new code with every remote click.



E-LOCK control panel buttons can be locked, providing better security.



DUAL SPEED two travel speeds provides greater control and performance.



SLIMLINE DESIGN designed for tight spaces. The opener only requires minimum side room of 40 mm.



PREMIUM AUTOMATIC SAFETY REVERSE function will allow your garage door to stop and reverse automatically if obstructed going down or stop going up.



TIMER-TO-CLOSE automatically closes the door after a pre-set amount of time.²



AUTOMATIC FORCE SENSING monitors and adjusts the force needed to open your garage with each operation.



MANUAL RELEASE CORD allows you to open your garage door whenever needed.

ACCESSORIES INCLUDED



FOUR BUTTON REMOTE CONTROLS

Premium remotes to control up to 4 garage doors or gates. Each button can be programmed to Security+ and Security+ 2.0 devices.

E970M



FOUR BUTTON WIRELESS WALL MOUNT REMOTE CONTROL

4 button wall remote to control garage doors, gates and myQ Remote LED Light. Easily programmed to Security+ and Security+ 2.0 devices.

E148M

POWERFUL ADD-ONS



MYQ CONNECTIVITY BUNDLE

Add monitoring and control away from home. Includes myQ Gateway and The Protector System™ (Safety IR Beams).

M828AU774



FOUR BUTTON CAR VISOR REMOTE CONTROL

Easily attaches to your car visor to control up to 4 garage doors or gates. Can be programmed to Security+ and Security+ 2.0 devices.

E964M



MYQ REMOTE LED LIGHT Ultra-bright LED light designed to illuminate your garage or workspace. Controlled by a garage door opener, remote control or myQ App.

827AU



WIRELESS SECURITY KEYPAD

Convenient and safe access to your garage without using a remote control or key.

E840M



KEY CABLE RELEASE

Allows the opener to be disengaged from your garage door when there is no power or a remote is not available.

CM1702

gomerlin.com.au ■ gomerlin.co.nz

¹Additional purchase of Merlin myQ Gateway and Safety IR Beams accessories required to enable myQ functionality. Visit gomerlin.com.au or gomerlin.co.nz for further information. ²Safety IR Beams must be installed to enable the use of Timer-to-Close. See User Guide for additional information.

WeatherDrive™

IDEAL FOR POWERING SHEDS AND CARPORT ROLLER DOORS
MR555MYQ




ROLLER GARAGE DOOR OPENER MYQ CAPABLE

Works with myQ² smart technology


Additional purchase of
The myQ Connectivity
Bundle is required.

APP AVAILABLE ON:




- Set real time notifications to alert you when your garage opens, closes or is left open.
- Monitor and control your garage door from anywhere.
- Share limited guest access with five people you trust.
- Pre-set scheduling to close your garage door at a certain time.
- Protect your loved ones and belongings with The Protector System™ (Safety IR Beams).
- Peace of mind knowing if your garage door is open or closed anywhere and any time.

TYPICAL INSTALLATION - ROLLER DOORS



- Maximum lifting under spring tensions: 15 kg
- Suitable for steel spring balanced doors
- Door height: 4.5m; total door area: 15m²
- Single dwelling, max door weight up to 100 kg



SECURITY



SECURITY+ 2.0®

- Encrypted rolling code across multiple frequencies.
- Security+ 2.0® technology virtually eliminates interference.

SMART



RADIO

- Provides 2-way communication from rolling door opener and accessories.
- Receiver with 64 memory registers.

ELECTRICAL



LIGHTING: LED LIGHTING

- LED light turns on with activation.
- Garage illumination: 9 premium ultrabright LEDs.

STANDARD SPECIFICATIONS

- IP34 housing
- myQ technology capable²
- Input Voltage: 240V AC
- Rated door areas up to: 15m²
- Max door height: 4.5m
- Max door weight: 100 kg
- Max peak pulling force: 500N
- Max lift under spring tension: 15 kg
- Minimum side room: 40mm
- Radio frequency: 433.30, 434.54 and 433.92 MHz with Security +2.0 technology.
- Noise rating 1M: 51DB
- Drum rotations: 5.5
- 24V DC motor with thermal overload protection
- Up to 64 memory registers
- Garage illumination: 12 premium ultrabright LEDs

Merlin®



AUSTRALIA

Chamberlain Australia Pty Ltd
PO Box 1446
Lane Cove NSW 1595
Australia

gomerlin.com.au
1800 638 234

NEW ZEALAND

Chamberlain New Zealand Ltd
PO Box 100-221
North Shore
Auckland 0745
New Zealand

gomerlin.co.nz
0800 653 667

Engineered and designed by The Chamberlain Group, Inc.
©2021 The Chamberlain Group, Inc.™ Trademark of The Chamberlain Group, Inc.
® Registered Trademark of The Chamberlain Group, Inc.



¹Based upon a 2.3m high door at regular speed setting. ²This feature requires monitored Safety IR Beams to be fitted. Linking your myQ account to partner may require an additional accessory purchase or subscription fee. Apple, the Apple logo, iPhone, and iPad are trademarks of Apple Inc., registered in the U.S. and other countries and regions. App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google LLC.